

Weak bond strength between successive layers in extrusion-based additive manufacturing

Emmanuel Keita, Hela Bessaies-Bey, Wenqiang Zuo, Patrick Belin, Nicolas
Roussel

► **To cite this version:**

Emmanuel Keita, Hela Bessaies-Bey, Wenqiang Zuo, Patrick Belin, Nicolas Roussel. Weak bond strength between successive layers in extrusion-based additive manufacturing. DiXite3dPrint : Fabrication Additive pour la Construction. Quelle Actualité Nationale?, École des Ponts ParisTech, Jan 2019, Champs-sur-Marne, France. hal-02119419

HAL Id: hal-02119419

<https://hal-enpc.archives-ouvertes.fr/hal-02119419>

Submitted on 3 May 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Baisse de la rigidité d'interface entre couches successives dans la construction additive par extrusion

Weak bond strength between successive layers in extrusion-based additive manufacturing

Emmanuel Keita¹, Hela Bessaies-Bey², Wenqiang Zuo¹, Patrick Belin¹ and Nicolas Roussel¹

1 : Laboratoire Navier
IFSTTAR/CNRS/ENPC, Université Paris-Est

2 : Laboratoire CPDM
IFSTTAR, Université Paris-Est

e-mail : emmanuel.keita@ifsttar.fr

Weak bond strength is often reported to result from a low level of intermixing between successive layers. It is often concluded that there seems to exist an upper limit either on structuration rate or on resting time between layers, above which thixotropy is at the origin of so-called “cold joints”. In parallel to intermixing issues, our results show that the superficial drying of the resting layer seems to also contribute to weaker interfaces bonds. We plot in the figure below the relative interface strength measured using a splitting test as a function of the resting time between layers for an interface protected from drying and an interface exposed to drying. The material is a W/C = 0.2 thixotropic mortar, for which the structuration rate A_{thix} was measured to be above 0.4Pa/s. We see that, even after 5 hours rest between layers, the interface strength is still higher than 90% of the reference interface strength if the material is protected from drying. However, if exposed to drying, the interface strength drops by 50% in a matter of a couple tens of minutes. As printable materials are often accelerated in order to improve their ability to quickly build up a structure, we can expect some increase in temperature resulting from this increase in chemical activity. This shall, in turn, increase drying rate and make these printable materials extremely sensitive to the external environment (temperature and humidity) or to the so-called printing environment.

Références

- [1] Emmanuel Keita, Hela Bessaies-Bey, Wenqiang Zuo, Patrick Belin and Nicolas Roussel, « Weak bond strength between successive layers in extrusion-based additive manufacturing: measurement and physical origin ». *Submitted*
-